

## emco Bau

### emco DIPLOMAT Original With ribbed carpet insert 517 R

<b>Model</b>	517 R
<b>Load</b>	Normal to heavy
<b>Support chassis</b>	Made using rigid aluminium with sound absorbing insulation on the underside
<b>Approx. height (mm)</b>	17
<b>Tread surface</b>	Recessed, robust, weather-proof, ribbed carpet strips.
<b>Standard profile clearance approx. (mm)</b>	5 mm, rubber spacers
<b>Automatic door systems</b>	Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005
<b>Slip resistance</b>	R 11 slip resistance as per DIN 51130
<b>Colours</b>	Anthracite no. 200 Brown no. 485 Light grey no. 220 Red no. 305 Sand no. 430
<b>Flammability</b>	Insert for Light Grey and Anthracite ribbed carpet colours available on request (surcharge applicable) with fire classification Cfl-s1 according to EN 13501.
<b>Connection</b>	Plastic-coated stainless steel cable
<b>Warranty</b>	
<b>Insert certified to TÜV PROFiCERT-product interior (Standard)</b>	French VOC regulation  LEED v4 (outside North America) BREEAM Exemplary Level Belgian VOC regulation AgBB (Committee for Health-related Evaluation of Building Products) MVV TB Appendix 8, 9 / ABG
<b>Pile material</b>	100% PP (polypropylene)
<b>Colour fastness to artificial light ISO 105-B02</b>	good 6
<b>Colour fastness to rubbing ISO 105 X12</b>	good 4
<b>Colour fastness to water ISO 105 E01</b>	good 5
<b>Dimensions</b>	Mat width:.....mm (bar length)

## Contact

Mat depth:.....mm (walking direction)

emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-  
49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-  
500 · Fax: +49 (0) 591/9140-852 · Email: [bau@emco.de](mailto:bau@emco.de) ·  
[www.emco-bau.com](http://www.emco-bau.com)