

## emco Bau

### emco DIPLOMAT Original Large With ribbed carpet insert and scraper bar 512 LRK

|                                                               |                                                                                                                                                                                                                   |
|---------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model                                                         | 512 LRK                                                                                                                                                                                                           |
| Load                                                          | Normal                                                                                                                                                                                                            |
| Support chassis                                               | Made using rigid aluminium with sound absorbing insulation on the underside                                                                                                                                       |
| Approx. height (mm)                                           | 12                                                                                                                                                                                                                |
| Tread surface                                                 | Recessed, robust, weather-proof, ribbed carpet strips, also with scraper bars mounted between the profiles.                                                                                                       |
| Standard profile clearance approx. (mm)                       | 5 mm, rubber spacers                                                                                                                                                                                              |
| Automatic door systems                                        | Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005                                                                                                           |
| Colours                                                       | Light grey no. 220<br>Anthracite no. 200<br>Red no. 305<br>Brown no. 485<br>Sand no. 430                                                                                                                          |
| Flammability                                                  | Insert for Light Grey and Anthracite ribbed carpet colours available on request (surcharge applicable) with fire classification Cfl-s1 according to EN 13501.                                                     |
| Connection                                                    | Plastic-coated steel cable                                                                                                                                                                                        |
| Warranty                                                      |                                                                                                                                                                                                                   |
| Insert certified to TÜV PROFiCERT-product interior (Standard) | French VOC regulation<br>LEED v4 (outside North America)<br>BREEAM Exemplary Level<br>Belgian VOC regulation<br>AgBB (Committee for Health-related Evaluation of Building Products)<br>MVV TB Appendix 8, 9 / ABG |
| Pile material                                                 | 100% PP (polypropylene)                                                                                                                                                                                           |
| Colour fastness to artificial light ISO 105-B02               | good 6                                                                                                                                                                                                            |
| Colour fastness to rubbing ISO 105 X12                        | good 4                                                                                                                                                                                                            |
| Colour fastness to water ISO 105 E01                          | good 5                                                                                                                                                                                                            |

**Dimensions**

Mat width:.....mm (bar length)

Mat depth:.....mm (walking direction)

**Contact**

emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-  
49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-  
500 · Fax: +49 (0) 591/9140-852 · Email: [bau@emco.de](mailto:bau@emco.de) ·  
[www.emco-bau.com](http://www.emco-bau.com)