

emco Bau

emco MARSCHALL Original With ribbed carpet insert and scraper bar 517 SRK

Model	517 SRK
Load	Extremely heavy
Support chassis	Reinforced support chassis made using rigid aluminium with sound absorbing insulation on the underside
Approx. height (mm)	17
Tread surface	Recessed, robust, weather-proof, ribbed carpet strips, also with scraper bars mounted between the profiles.
Standard profile clearance approx. (mm)	5 mm, rubber spacers
Automatic door systems	Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005
Colours	Light grey no. 220 Anthracite no. 200 Red no. 305 Brown no. 485 Sand no. 430
Flammability	Insert available on request (surcharge applicable) with fire classification Cfl-s1 according to EN 13501.
Connection	Plastic-coated stainless steel cable
Warranty	
Insert certified to TÜV PROFiCERT-product interior (Standard)	French VOC regulation LEED v4 (outside North America) BREEAM Exemplary Level Belgian VOC regulation AgBB (Committee for Health-related Evaluation of Building Products) MVV TB Appendix 8, 9 / ABG
Pile material	100% PP (polypropylene)
Colour fastness to artificial light ISO 105-B02	good 6
Colour fastness to rubbing ISO 105 X12	good 4
Colour fastness to water ISO 105 E01	good 5
Dimensions	Mat width:.....mm (bar length)

Contact

Mat depth:.....mm (walking direction)

emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-
49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-
500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de ·
www.emco-bau.com