

## emco Bau

### emco MARSCHALL Original Large With ribbed carpet insert and brush strip 522 SLRB

|                                                 |                                                                                                                                                                                    |
|-------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model                                           | 522 SLRB                                                                                                                                                                           |
| Load                                            | Extremely heavy                                                                                                                                                                    |
| Support chassis                                 | Reinforced support chassis made using rigid aluminium with sound absorbing insulation on the underside                                                                             |
| Approx. height (mm)                             | 22                                                                                                                                                                                 |
| Tread surface                                   | Recessed, robust, weather-proof, ribbed carpet strips, also with brush strips mounted between the profiles.                                                                        |
| Standard profile clearance approx. (mm)         | 5 mm, rubber spacers                                                                                                                                                               |
| Automatic door systems                          | Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005                                                                            |
| Colours                                         | Light grey no. 220<br>Anthracite no. 200<br>Red no. 305<br>Brown no. 485<br>Sand no. 430<br>grey<br>Black                                                                          |
| Flammability                                    | Insert available on request (surcharge applicable) with fire classification Cfl-s1 according to EN 13501.                                                                          |
| Connection                                      | Plastic-coated steel cable                                                                                                                                                         |
| Warranty                                        |                                                                                                                                                                                    |
| Pile material                                   | 100% PP (polypropylene)                                                                                                                                                            |
| Colour fastness to artificial light ISO 105-B02 | good 6                                                                                                                                                                             |
| Colour fastness to rubbing ISO 105 X12          | good 4                                                                                                                                                                             |
| Colour fastness to water ISO 105 E01            | good 5                                                                                                                                                                             |
| Dimensions                                      | Mat width:.....mm (bar length)<br>Mat depth:.....mm (walking direction)                                                                                                            |
| Contact                                         | emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · www.emco-bau.com |