

emco Bau

emco DIPLOMAT Premium With MAXIMUS insert 512 P Maximus

Model	512 P Maximus
Load	Normal
Support chassis	Made using rigid aluminium with Premium sound absorbing insulation on the underside
Approx. height (mm)	12
Note on height	The insert can actually be approx. 2-3 mm higher due to the wear layer.
Tread surface	The stylish Maximus insert stands out from the crowd with its premium-quality tufted velour and high-end design.
Standard profile clearance approx. (mm)	5 mm, rubber spacers
Automatic door systems	Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005
Slip resistance	R 12 slip resistance as per DIN 51130
Colours	Anthracite 80.02 Brown 80.04 Red 80.07 Black mottled 81.01 Black 80.01
Special colours	Other colours from our clean-off collection also available.
Flammability	Fire classification for the complete mat system Bfl-s1 in accordance with EN 13501
Connection	Plastic-coated stainless steel cable
Warranty	5 years guarantee
Insert certified to TÜV PROFiCERT-product interior (Standard)	French VOC regulation LEED v4 (outside North America) BREEAM Exemplary Level Belgian VOC regulation AgBB (Committee for Health-related Evaluation of Building Products) MVV TB Appendix 8, 9 / ABG
Pile material	100% PA 6.6 (polyamide)
Use classification EN1307	class 33 (heavy commercial use)
Colour fastness to artificial light ISO 105-B02	good 5-6

Colour fastness to rubbing ISO 105 X12 good 5

Colour fastness to water ISO 105 E01 good 5

Bacterial reduction EHEC ASTM-e2149 29,4 %

Bacterial reduction staphylococcus aureus ASTM-e2149 16,7 %

Bacterial reduction klebsiella pneumoniae ASTM-e2149 68,2 %

Dimensions

Mat width:.....mm (bar length)

Mat depth:.....mm (walking direction)

Contact

emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · www.emco-bau.com